

## 5H 欧规、陶瓷管、高分断、慢熔断 Functional Characteristics 电气特性

測試電流 Testing current	熔斷時間 Blow Time	
	Min 最小	Max 最大
150%	1h	/
210%	/	30s
275%	750ms	80s
400%	95ms(2A-3.15A) 150ms (4A-10A)	5s
1000%	10ms	150ms
	<b>Breaking Capacity 分断能力</b>	
	1500A at 250V AC (1A-10A)	
	<b>Material 材料</b>	
	Fuse body –CERAMIC TUBE	
	End cap--nickel plated brass	
	Pigtail--tin plated copper on nickel plated brass cap	

## Approvals 认证 (○ Pending ● Approvals)

額定電流 Current Rating	額定電壓 Voltage Rating	認證 Approvals		
				
1A	250V	○	○	○
1.25A	250V	○	○	○
1.6A	250V	○	○	○
2A	250V	○	○	○
2.5A	250V	○	○	○
3.15A	250V	○	○	○
4A	250V	○	○	○
5A	250V	○	○	○
6.3A	250V	○	○	○
8A	250V	○	○	○
10A	250V	○	○	○

## 5C 欧规、陶瓷管、高分断、快熔断 Functional Characteristics 电气特性

測試電流 Testing current	熔斷時間 Blow Time	
	Min 最小	Max 最大
150%	1h	/
210%	/	30s
275%	10ms(2A-6.3A) 40ms(8A-10A)	2s(2A-4A) 3s(5A-6.3A) 20s(8A-10A)
400%	3ms(2A-6.3A) 10 ms (8A-10A)	300ms(2A-6.3A) 1s(8A-10A)
1000%	/	20ms(2A-6.3A) 30ms(8A-10A)
	<b>Breaking Capacity 分斷能力</b>	
	1500A at 250V AC (1A-10A)	
	<b>Material 材料</b>	
	Fuse body –CERAMIC TUBE	
	End cap--nickel plated brass	
	Pigtail--tin plated copper on nickel plated brass cap	

**Approvals 认证 (○ Pending ● Approvals)**

額定電流 Current Rating	額定電壓 Voltage Rating	認證 Approvals		
				
1A	250V	○	○	○
1.25A	250V	○	○	○
1.6A	250V	○	○	○
2A	250V	○	○	○
2.5A	250V	○	○	○
3.15A	250V	○	○	○
4A	250V	○	○	○
5A	250V	○	○	○
6.3A	250V	○	○	○
8A	250V	○	○	○

10A	250V	○	○	○
-----	------	---	---	---

5SH 美规、陶瓷管、慢熔断 Functional Characteristics 电气特性

測試電流 Testing current	熔斷時間 Blow Time	
	Min 最小	Max 最大
100%	4h	/
135%	/	1h
200%	/	120s
	<b>Breaking Capacity 分断能力</b>	
	10,000 amperes at 125V AC (1A-12A)	
	35 amperes at 250V AC (0-1A)	
	100 amperes at 250V AC (1.1A-3.5A )	
	200 amperes at 250V AC (3.6A-15A )	
	<b>Material 材料</b>	
	Fuse body –CERAMIC TUBE	
	End cap--nickel plated brass	
Pigtail--tin plated copper on nickel plated brass cap		

Approvals 认证 (○ Pending ● Approvals)

額定電流 Current Rating	額定電壓 Voltage Rating	認證 Approvals	
			
1A	125V/250V	●	
2A	125V/250V	●	
2.5A	125V/250V	●	
3A	125V/250V	●	
3.5A	125V/250V	●	
4A	125V/250V	●	
5A	125V/250V	●	
6A	125V/250V	●	
8A	125V/250V	●	
10A	125V/250V	●	
12A	125V/250V		●

5GH 美规、陶瓷管、快熔断 Functional Characteristics 电气特性

測試電流 Testing current	熔斷時間 Blow Time	
	Min 最小	Max 最大
100%	4h	/
135%	/	1h
200%	/	5s
	<b>Breaking Capacity 分斷能力</b>	
	10,000 amperes at 125V AC (1A-15A)	
	35 amperes at 250V AC (0-1A)	
	100 amperes at 250V AC (1.1A-3.5A )	
	200 amperes at 250V AC (3.6A-15A )	
	<b>Material 材料</b>	
	Fuse body –CERAMIC TUBE	
	End cap--nickel plated brass	
	Pigtail--tin plated copper on nickel plated brass cap	

**Approvals 认证 ( ◯ Pending • Approvals )**

額定電流 Current Rating	額定電壓 Voltage Rating	認證 Approvals	
			
1A	125V/250V	•	
2A	125V/250V	•	
2.5A	125V/250V	•	
3A	125V/250V	•	
3.5A	125V/250V	•	
4A	125V/250V	•	
5A	125V/250V	•	
6A	125V/250V	•	
8A	125V/250V	•	
10A	125V/250V	•	
12A	125V/250V		•
15A	125V/250V		•